

BQ-EX-UFC-UFO

Aluminum tag plate for UFC and UFO self-regulating heating cables. To be installed if T-class compliance was proven by stabilized design and not by unconditional T-rating.
 PN: 2000-BQ35 Weight: 0.04 kg

BQ-EX-FXT

Aluminum tag plate. To be installed when parallel constant wattage FMT or FHT heating cables are used in hazardous areas.
 PN: 2000-BQ36 Weight: 0.04 kg

BQ-LABEL-EX


Aluminum tag plate. To be installed when series polymer insulated XPI & XPI-S heating cables are used in hazardous areas.
 PN: 2000-BQ37 Weight: 0.04 kg

BQ-LABEL-NH

Aluminum tag plate. To be installed when series polymer insulated XPI & XPI-S heating cables are used non hazardous areas. This label is not mandatory but highly recommended for future reference.
 PN: 2000-BQ38 Weight: 0.04 kg


PIPE STRAPS

Metal straps for pipe mounting of integrated power connections, above the insulation tees and end seals as well as support brackets and the tubular insulation entry.
 Banding: stainless steel



Pipe outer diameter in mm	(inches)	Pipe strap	PN (Weight)
20 - 47	(1/2" - 1 1/4")	PSE-047	2000-PS01 (0.017 kg)
40 - 90	(1 1/4" - 3")	PSE-090	2000-PS02 (0.024 kg)
60 - 288	(2" - 10")	PSE-280	2000-PS03 (0.052 kg)
60 - 540	(2" - 20")	PSE-540	20000PS04 (0.052 kg)

PROTECTIVE GROMMET




G-02

Silicone grommet that protects the heating cable at sharp edges such as endplates of insulation cladding, flanges etc. It can be cut-to-length and resists temperatures up to 215°C.
 Sold in pieces of 1 m.

PN: 2000-ZKT Weight: 0.37 kg/m

FIXING MATERIALS

Self-adhesive tape for fixing the heating cables on pipes or other equipment.



GT-66

Glass cloth tape for attaching heating cable to pipe.
 Not for stainless steel pipes or for installation temperatures below 5°C.
 20 m per roll, 12 mm width.
 PN: 2000-1066 Weight: 0.053 kg

GS-54

Glass cloth tape with silicone adhesive system (<5ppm leachable halide) for attaching heating cable to pipe.
 For stainless steel pipes or for any installation below 5°C.
 16 m per roll, 12 mm width.
 PN: 2000-1054 Weight: 0.048 kg